



RE111QTAB

Rugged Tablet PC



Android



IP 65



GPS



High - capacity



Bluetooth



1D



2D



NFC



3G/ 4G



WIFI

★ FEATURES

- Support for Android 9.0 system
- Integrated 3G/4G all network communication, WiFi, Bluetooth and other communication modes
 - 8000mAh battery, 6-8 hours of machine endurance
 - IP65 high protection level, in accordance with MIL-STD-810G
 - Support GPS, GLONASS, more accurate positioning
- Support 13 million pixel auto focus camera, easy to collect images and video information
 - Support 1D/2D, NFC and other functional modules for free selection



RE111QTAB

Rugged Tablet PC



☆ PRODUCT VIEWS



☆ OPTIONAL ACCESORIES



Docking Charger



Hand-strap



Vehicle Mount



RE111QTAB

Rugged Tablet PC



SPECIFICATION

Basic parameters		Performance parameter	
Dimension	275.5 x 187.5 x 22mm	CPU	MSM 8953
Weight	device unit 970g	OS	Android 9.0
Device Color	black	RAM	64GB
LCD	10.1inch IPS 16:10, 800*1280	ROM	4GB LPDDR3
Touch Panel	10 points Capacitive, G+G	Battery	
Camera	Front 5.0MP Rear 13.0MP	Capacity	3.7V/8000mAh
I/O	USB 2.0 x 1, Type C x 1, SIM Card x 1, TF Card x 1, HDMI 1.4a x 1, 12pins Pogo Pin x 1, Φ3.5mm standard earphone jack x 1, Φ3.5mm DC jack x 1	Type	Built-in Li-polymer battery
Power	AC100V ~ 240V, 50Hz/60 Hz output DC 5V/3A	Endurance	8hrs (50% volume sounds, 50% brightness, 1080P HD video display by default)
GPS	support GPS, glonass	Network connections	
Optional modules		WIFI	2.4G+5G dual frequency, WIFI 802.11(a/b/g/n/ac)
NFC	Support ISO/IEC 14443A protocol Card reading distance:3-5cm	Bluetooth	BT4.1 (BLE)
1D	MOTO SE655E100R, Optical Position: 5mil, Scan speed: 50 times/s	3G/4G	LTE FDD: B1/B3/B5/B7/B8/B20 LTE TDD: B38/B40/B41 WCDMA: B1/B2/B5/B8 GSM: 850/900/1800/1900MHz
2D	Honeywell N3680, Optical Position: 5mil, Scan speed: 50 times/s	Reliability	
		Operate Temperature	-10 °C ~ 50 °C
		Store Temperature	-20 °C ~ 60 °C
		Humidity	IP65
		IP Grade	95% Non-Condensing