

ETX-15R2 Series

POS All In One







ETX-15R2 All In One POS

Desktop POS Terminal
Digitalized Retail New Experience
High Performance, Low Power Consumption Processors
Full Aluminum Alloy Build
15.6"Ultra-Slim Framed FHD Display
Foldable Design
Comprehensive Interfaces



Specifications

Performance Parameters CPU Intel Core is Series Intel Core is Series Mindows 11/10 Memory 4/8GB DDR+64/128/256/512GB SSD Main Display 15.6° FHD Capacitive Multi-Touch Screen, 1920*1080 Customer Display (optional) USB 2 x USB3.0 + 3 x USB2.0 Serial Port 1 x DB9 Ethernet Interface 1 x RJ45 Display Interface 1 x VGA Parameters Audio Jack 1 x 3.5mm Headphone Jack 1 x 3.5mm Microphone Jack 1 x 3.5mm Microphone Jack Power 1 x \phi5.5mm DC Jack Key Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Wi-Fi (optional) IEEE 802.11 b/g/n, 2.4GHz Environment Humidity 5% ~ 95%RH (No condensation) ESD 48 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from Microsoft.com when needed.			
Performance Parameters OS Windows 11/10 Memory 4/8GB DDR+64/128/256/512GB SSD Main Display 15.6" FHD Capacitive Multi-Touch Screen, 1920*1080 Customer Display (optional) USB 2 x USB3.0 + 3 x USB2.0 Serial Port 1 x DB9 Ethernet Interface 1 x VGA Parameters Parameters Audio Jack 1 x 3.5mm Headphone Jack 1 x 3.5mm Microphone Jack 1 x 3.5mm Microphone Jack 1 x 3.5mm Microphone Jack 1 x 5.5mm DC Jack Rey Power 1 x 65.5mm DC Jack Rey Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm TCP/IP 100M/1000M Wireless Data Communication Bluetooth (optional) Ethernet			Intel Celeron J6412
Parameters OS Windows 11/10 Memory 4/8GB DDR+64/128/256/512GB SSD Main Display 15.6" FHD Capacitive Multi-Touch Screen, 1920*1080 Customer Display (optional) 10.1" HD 1024×600 USB 2 x USB3.0 + 3 x USB2.0 Serial Port 1 x DB9 Ethernet Interface 1 x VGA Parameters Physical Power 1 x x 9.5mm Headphone Jack 1 x 3.5mm Microphone Jack 1 x 3.5mm Microphone Jack 1 x 3.5mm Microphone Jack 1 x 5.5mm DC Jack Key Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Wi-Fi (optional) IEEE 802.11 b/g/n, 2.4GHz Environment Parameters Working Temperature P°C ~ +40°C Storage Temperature 20°C ~ +60°C Humidity 5% ~ 959RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from			Intel Core i3 Series
OS Windows 11/10 Memory 4/8GB DDR+64/128/256/512GB SSD Main Display 15.6° FHD Capacitive Multi-Touch Screen, 1920*1080 Customer Display (optional) 10.1° HD 1024×600 USB 2 x USB3.0 + 3 x USB2.0 Serial Port 1 x DB9 Ethernet Interface 1 x RJ45 Display Interface 1 x VGA Audio Jack 1 x 3.5mm Headphone Jack 1 x 3.5mm Microphone Jack 1 x 5.5mm DC Jack Key Power key Notification 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet 1 CP/IP 100M/1000M Wireless Data 2 Wi-Fi (optional) EEE 802.11 b/g/n, 2.4GHz Environment (optional) Bluetooth BT4.2 + BLE Working Temperature 20°C ~ +40°C Storage Temperature 20°C ~ +60°C Humidity 5% ~ 959RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from			Intel Core i5 Series
Main Display 15.6" FHD Capacitive Multi-Touch Screen, 1920*1080		OS	Windows 11/10
Customer Display (optional) USB 2 x USB3.0 + 3 x USB2.0 Serial Port 1 x DB9 Ethernet Interface 1 x VGA Parameters Audio Jack 1 x 3.5mm Headphone Jack 1 x 3.5mm Microphone Jack 1 x 3.5mm DC Jack Rey Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Wi-Fi (optional) IEEE 802.11 b/g/n, 2.4GHz Environment Parameters Accessories Working Temperature 2°C ~ +40°C Storage Temperature 2°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Memory	4/8GB DDR+64/128/256/512GB SSD
Physical Parameters Physical Parameters Power Power Power Notification Pirenet (optional) Wireless Data Communication Parameters Parameters Working Temperature Parameters Note Note Note 1. Physical (optional) Poser Note Power Notification Power Notif		Main Display	15.6" FHD Capacitive Multi-Touch Screen, 1920*1080
Optional USB 2 x USB3.0 + 3 x USB2.0		Customer Display	10.1" HD 1024×600
Serial Port 1 x DB9 Ethernet Interface 1 x RJ45 Display Interface 1 x VGA Audio Jack 1 x 3.5mm Headphone Jack 1 x 3.5mm Microphone Jack Power 1 x φ5.5mm DC Jack Key Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Bluetooth (optional) EEE 802.11 b/g/n, 2.4GHz Environment Arameters Humidity 5% ~ 95%RH (No condensation) EsD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Accessories Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		(optional)	
Ethernet Interface1 x RJ45Display Interface1 x VGAAudio Jack1 x 3.5mm Headphone JackPower1 x φ5.5mm DC JackKeyPower keyNotificationTone, LEDAudio1 x SpeakerDimensions379mm×179mm×313mmEthernetTCP/IP 100M/1000MWireless DataWi-Fi (optional)IEEE 802.11 b/g/n, 2.4GHzCommunicationBluetooth (optional)Bluetooth BT4.2 + BLEWorking Temperature0°C ~ +40°CStorage Temperature -20°C ~ +60°CHumidity5% ~ 95%RH (No condensation)ESD±8 kV air discharge, ±4 kV direct dischargeStandardPower Adapter×1Face Recognition CameraOptionalMSR NFCNote1. Physical interfaces of different processors may be different, please take the physical goods shall prevail.2. The version of Window OS is not activated, please buy license from		USB	2 x USB3.0 + 3 x USB2.0
Physical Parameters Audio Jack Audio Jack Power 1 x φ5.5mm Microphone Jack Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Wi-Fi (optional) Bluetooth (optional) Bluetooth BT4.2 + BLE Working Temperature 0°C ~ +40°C Storage Temperature -20°C ~ +60°C Humidity Sw ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Accessories Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Serial Port	1 x DB9
Parameters Audio Jack Audio Jack 1 x 3.5mm Microphone Jack 1 x 95.5mm DC Jack Rey Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Wireless Data Communication Bluetooth (optional) Bluetooth BT4.2 + BLE Working Temperature 0°C ~ +40°C Storage Temperature 20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Ethernet Interface	1 x RJ45
Audio Jack Power 1 x φ5.5mm DC Jack Key Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Bluetooth (optional) Bluetooth BT4.2 + BLE Working Temperature Parameters Working Temperature -20°C ~ +40°C Storage Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Display Interface	1 x VGA
Power 1 x φ5.5mm DC Jack		Audio Jack	1 x 3.5mm Headphone Jack
Key Power key Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Wi-Fi (optional) IEEE 802.11 b/g/n, 2.4GHz Communication Bluetooth Bluetooth BT4.2 + BLE Working Temperature 0°C ~ +40°C Environment Parameters Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera MSR NFC Note Note Note Note 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from			1 x 3.5mm Microphone Jack
Notification Tone, LED Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Bluetooth (optional) IEEE 802.11 b/g/n, 2.4GHz Environment Parameters Working Temperature 0°C ~ +40°C Storage Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Power	1 x φ5.5mm DC Jack
Audio 1 x Speaker Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Bluetooth (optional) Working Temperature 0°C ~ +40°C Environment Parameters Working Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Key	Power key
Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wireless Data Communication Bluetooth (optional) Environment Parameters Accessories Optional Note Dimensions 379mm×179mm×313mm Ethernet TCP/IP 100M/1000M Wi-Fi (optional) IEEE 802.11 b/g/n, 2.4GHz Bluetooth BT4.2 + BLE Optional Bluetooth BT4.2 + BLE Optional Note Note Optional For a parameters Accessories Optional Note Dimensions 379mm×179mm×313mm TCP/IP 100M/1000M BEEE 802.11 b/g/n, 2.4GHz Accessories Optional Bluetooth BT4.2 + BLE Optional Note Note Note Optional For a parameters Accessories Optional MSR NFC I. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Notification	Tone, LED
Wireless Data Communication Bluetooth (optional) Working Temperature Parameters Environment Parameters Accessories Optional Accessories Note Ethernet TCP/IP 100M/1000M Wi-Fi (optional) Bluetooth BT4.2 + BLE Bluetooth BT4.2 + BLE Bluetooth BT4.2 + BLE Working Temperature O°C ~ +40°C Storage Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Face Recognition Camera MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Audio	1 x Speaker
Wireless Data Communication Bluetooth (optional) Bluetooth BT4.2 + BLE Working Temperature 0°C ~ +40°C Storage Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Dimensions	379mm×179mm×313mm
Communication Bluetooth (optional) Bluetooth BT4.2 + BLE Working Temperature 0°C ~ +40°C Storage Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Ethernet	TCP/IP 100M/1000M
Coptional Bluetooth BT4.2 + BLE		Wi-Fi (optional)	IEEE 802.11 b/g/n, 2.4GHz
(optional) Working Temperature 0°C ~ +40°C Storage Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Bluetooth	Bluetooth BT4.2 + BLE
Environment Parameters Storage Temperature -20°C ~ +60°C Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		(optional)	
Parameters Humidity 5% ~ 95%RH (No condensation) ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Working Temperature	0°C ~+40°C
Accessories ESD ±8 kV air discharge, ±4 kV direct discharge Standard Power Adapter×1 Face Recognition Camera Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from	Environment	Storage Temperature	-20°C ~ +60°C
Accessories Standard Power Adapter×1 Face Recognition Camera MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from	Parameters	Humidity	5% ~ 95%RH (No condensation)
Accessories Optional Face Recognition Camera MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		ESD	±8 kV air discharge, ±4 kV direct discharge
Accessories Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from	Accessories	Standard	Power Adapter×1
Optional MSR NFC 1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from			Face Recognition Camera
1. Physical interfaces of different processors may be different, please take the physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from		Optional	MSR
Note physical goods shall prevail. 2. The version of Window OS is not activated, please buy license from			NFC
Note 2. The version of Window OS is not activated, please buy license from	Note	1. Physical interfaces	of different processors may be different, please take the
2. The version of Window OS is not activated, please buy license from		physical goods shall prevail.	
Microsoft.com when needed.		2. The version of Window OS is not activated, please buy license from	
		Microsoft.com whe	en needed.